



GEOTECHNICAL PROPERTIES OF CONTAMINATED SOIL

Neelam Phougat *

Central Soil & Materials Research Station Olof plame Marg, Hauz Khas, New Delhi-110016

ARTICLE INFO

Article History:

Received 9th April, 2017
Received in revised form 25th
May, 2017 Accepted 10th June, 2017
Published online 28th July, 2017

Key words:

Industrial waste, contamination, geotechnical properties, soil, petroleum products, acid, alkali, salt, industrial effluent.

ABSTRACT

Geotechnical properties of soil get modified on contamination with industrial wastes and garbage. Extent of modification of geotechnical properties of soil depends on chemical composition of the contaminant and soil and amount of contaminant present in soil. Depending on the nature of contaminant, positive or negative effects of contaminant on the engineering properties of soils are possible. Detrimental effect of contaminated soil can cause foundation failures resulting in considerable damage to the structure built on it. On addition of some industrial waste, such as textile effluent, engineering properties of soil get improved. In this review, effect of petroleum products, acids, alkalis, salts and industrial effluents on engineering properties of soil is being discussed.

Copyright © Neelam Phougat. 2017, This is an open-access article distributed under the terms of the Creative Commons Attribution License, which permits unrestricted use, distribution and reproduction in any medium, provided the original work is properly cited.

INTRODUCTION

Industries, such as, soap industries, iron and steel industries, tanneries, textile industries, generate large amounts of solid and liquid waste. Improper disposal of industrial wastes and garbage on to the land contaminates the soil and the ground water. The contaminant may be acids, alkali, salts, metals or organic matters. Soil, being electro-chemically active, reacts with contaminant [1]. Physicochemical interaction of soil with contaminant modifies geotechnical properties of soil. Conventional geotechnical principles cannot be applied to contaminated soil. Extent of modification of soil properties due to contamination depend on the quantity and chemical composition of the contaminant, partition coefficient and mineralogy, pore fluid chemistry, permeability and adsorption properties of the soil [2-6]. Contaminant changes the properties of soil by affecting the dielectric constant, electrolyte concentration, ion exchange capacity and thickness of diffuse double layer. With increase in dielectric constant, interparticle shearing resistance decreases and liquid limit and double layer thickness of soil increases.

Detrimental effect of contaminated soil can cause extensive cracking damage to the floors, pavements and severe foundation failures resulting in considerable damage to structure built on it. Because of lack of space due to rapid urbanisation, contaminated lands are

reclaimed to construct buildings and infrastructures. Foundation problems were being faced due to presence of compressible materials beneath the buildings of Mexico city. Contaminant dissolved in rain water percolate the soil and damage foundation of buildings. Reduction of soil porosity and bearing capacity and increases in settlement due to soil contamination may result in failures of existing structures [7]. Because of increase in compression index and swelling index of contaminated clay extra settlement is observed on new structure loading [8,9]. The review of available literature suggests that before constructing building, road, bridge, embankment, dam etc. on contaminated soil, effect of contaminant on soil strength is to be studied. If suitable remedial measures and precautions are not undertaken then contaminated soil may cause failure of structure built on it causing catastrophic damage.

Effect of some of the contaminant on geotechnical properties of soil is reviewed below:

Contamination with petroleum and refinery products

Geotechnical properties of soil get modified on contamination with petroleum and refinery products [10]. Contamination of soil with crude oil has deteriorating effect on its strength, permeability, plasticity and swelling characteristics [11, 12].

*Corresponding author: Neelam Phougat

Central Soil & Materials Research Station Olof plame Marg, Hauz Khas, New Delhi-110016

Due to oil contamination, permeability, shear strength and Atterberg limits of CL (clay of low plasticity) soil got reduced [12]. A direct correlation between oil content and angle of internal friction in clay CL soil and inverse correlation between oil content and angle of internal friction in SP (poorly graded sand) and SM (silty sand) soils is reported by Mashalah *et al.* [12]. With increasing oil content in soil, cohesion is reduced due to loose packing of clay particles. It is reported that on contamination with 16% of oil content, CL samples changed from hard consistency to soft consistency [13]. Dorota Izdebska-Mucha *et al.* [14] reported that microstructure of clay on contamination with diesel oil became more isotropic and in comparison to uncontaminated clay, aggregates formed were having relatively loose packing of clay particles. The contaminated clay behaves more like a cohesionless material [1]. On getting permeated with heptanes, permeability of kaolinite was increased to about 1000 times [15].

The effect of motor oil contamination on the geotechnical characteristics of over-consolidated clay (CH) was studied by Nazir for a period of 24 months [16]. Atterberg limits, which determine the consistency of the soils on changes in wetting conditions, were decreased significantly with increasing the duration of oil contamination up to first 3 months, after which, they remain constant due to stabilization of clay structure. Viscosity of motor oil influences the Atterbergs limit thus lowering it. The coefficient of permeability of contaminated clay increased significantly to three times the value for uncontaminated clay at low stress range of 100 and 200 kPa, that is almost the pre-consolidation pressure. This trend exhibits direct proportion with increasing duration of contamination up to first 3 months. At stress range higher than pre-consolidation stress, minor effect on the coefficient of permeability was reported on increasing the duration of contamination up to 24 months. The increase in permeability of contaminated clay is attributed to the reduction in the thickness of the double layer that surrounds the clay particle. Dielectric constant of motor oil is lower than that of water. Low dielectric constant of pore fluid of clay contaminated with motor oil causes shrinkage of double layer [17,18]. Macrospores and cracks developed on soil shrinkage resulted in an increase in coefficient of permeability. Compression index and swelling index of contaminated clay increased with increasing duration of contamination up to first 6 months and after that these indexes became almost constant due to reorientation of structural element [14].

Unconfined compressive strength of clay contaminated with motor oil was reduced by about 38% as compared to the uncontaminated clay. Unconfined compressive strength kept on decreasing up to first 6 months of duration of contamination and after that it attained constant value. Loose packing of clay particles due to contamination with motor oil caused the reduction in unconfined compressive strength of clay. The stress history of over consolidated clay is not affected by the oil contamination because oil contamination has minor effect on over-consolidation ratio. The effect of oil contamination on geotechnical properties of over-

consolidated clay was significant up to first 6 months of contamination and beyond that the effect was very insignificant.

Stiffness and permeability of the clay is reported to get decreased on contamination with crude oil [19]. Load carrying capacity of sand contaminated with oil decreased and it further decreased with increase in oil content [20,21].

Geotechnical properties of the lateritic soil contaminated with crude oil changes remarkably [22]. Crude oil spills degrade lateritic soil [23]. Lateritic soil is a highly weathered natural material rich in oxides of iron, aluminium, manganese and/ or titanium [19, 21, 23]. Crude oil is a mixture of water, hydrocarbon and organic compounds of sulphur, nitrogen and oxygen which varies in composition from place to place [24]. Variation in the composition of crude oil affects the extent to which the geotechnical properties of lateritic soil are to be changed [19]. Maximum dry density (MDD) and the optimum moisture content (OMC) of lateritic soil decreased on contamination with crude oil and it further decreased with time [21]. Optimum moisture content and the maximum dry density of lateritic soil reduced from 11.40% and 1.98g/cm³ to 9.50% and 1.81g/cm³, respectively on contamination with crude oil. On contamination with crude oil, optimum moisture content value of lateritic soil got reduced by 17% and the maximum dry density value reduced by 9%. The adsorption of crude oil onto the lateritic soil surfaces agglomerate the lateritic soil particles thereby reducing the specific surface area, leading to the reduction in the bond strength of the lateritic soil.

The particle size was increased on contamination of lateritic soil with crude oil because the crude oil clod to the soil particles. The percentage of fines was reduced with increase in the oil content because the oil clod to different particles and prevents them from successfully passing through sieve. The grain size distribution of same soil sample in the same sieve sizes changes on varying the percentages of crude oil in the soil [25]. Liquid limit (LL) and plastic limit (PL) of lateritic soil reduces on contamination with crude oil [26]. The Atterbergs limit decreased due to reduction in the cation exchange capacity (CEC) of the soil. The decrease in the value of Atterbergs limit of the contaminated soil was due to changes in cohesive forces between the particles of the lateritic soil. The Atterberg limit decreased with increase in oil percentage. The Liquid Limits (LL) of uncontaminated soil and soil contaminated with crude oil was 29.00 and 16.04 respectively.

Unconfined compressive strength and bearing capacity of soil contaminated with crude oil decreases and soil become unsuitable for supporting engineering structures [21]. The value of California Bearing Ratio (CBR) of the uncontaminated soil was higher than that of the contaminated soil. The CBR of soil contaminated with crude oil was reduced by 50%. On burning of oil spilled on soil surface, tar mat oily scum was formed which retarded soil aeration and water infiltration into subsoil layers [27].

Geotechnical properties of clay soil changes on contamination with crude oil [28, 29]. Liquid limit, plastic limit and plasticity index of soft clay contaminated with crude oil increased by 17.9%, 6.9% and 37.5% respectively. In contaminated clay more water is to be added to change its consistency level. On contamination with crude oil, maximum dry density of soft clay increased sharply at relatively low optimum moisture content. Bulk density of contaminated clay increased linearly with sorption time. Total hydrocarbon content (THC) of crude oil influences sorption process and geotechnical properties of soft clay soils. Light crude oil samples (low value of THC) has lesser influence on the bulk density and porosity of soft clay soils than heavier crude oil samples. Due to reduction of pore sizes of the clay soil by the adsorbed oil, porosity of contaminated clay decreases with increase in sorption time and crude oil hydrocarbon content. Permeability of contaminated clay was also reduced.

The rate of swelling of soft clay contaminated with oil was lower than that of uncontaminated clay [1]. The swelling pressure exerted by the soft clay contaminated with oil was lower than (about 32%) that exerted by the uncontaminated soft clay and it decreases with increase in both sorption time and crude oil hydrocarbon content. The strength of contaminated soft clay was dependent on confining pressure. At low confining pressures, strength of the contaminated soft clay was less than that of the uncontaminated clay but the strength was slightly higher than that of the uncontaminated clay at high confining pressures. High strength of the crude oil contaminated soft clays may be due to the increased bonding of soil particles in the presence of oil.

Spent engine oil (SEO), also known as waste engine oil, is generally obtained after servicing of automobile and generator engines [30]. Spent engine oil contains hydrocarbons and heavy metals [31]. Spent engine oil was mixed with soil and its effect on soil properties was investigated by Atuanya and Okonokhua *et. al.* [32, 33]. Contamination of soil with SEO had no effect on pH of the soil. Compared to uncontaminated soil, concentration of organic C, N and Mg in the contaminated soils got increased and concentration of P got decreased [34]. The oil-contaminated soils contained more heavy metals than the uncontaminated soil and on increasing the concentration of oil, concentration of heavy metals (Fe, Cu, Co, Zn and Pb) in soil got increased [35]. Metal get attached to the surface of the soil due to electrostatic attraction between positively charged metals and negatively charged clay particles [36].

Contamination with acids and alkalis

Contamination of soil with acids and bases can cause foundation failure [37,38]. Cracking of floors, pavements and beams and upheaval of foundations in a fertilizer plant was found to be due to phosphoric acid as the source of contamination [39]. High phosphate content in acidic environment caused heaving of soil. Differential movement were observed in lightly and unevenly loaded structures. Hydraulic conductivity of kaolinite was reduced when it got contaminated with acetic acid.

Clay was treated with sulfuric acid solution for different periods of time, ranging from 1 to 9 months. Compressibility of clay increased significantly with a decrease in pH values. In acidic medium, the compressibility of clay increased due to the collapse of the diffuse double layer [40].

Kawasaki mud that contains montmorillonite and Yurakucho silt that has kaolinite as the dominant clay mineral were treated with solutions of sulfuric acid for a period of 300 days. Undrained triaxial compression tests were conducted on treated samples. Soil strength of Kawasaki mud increased on decreasing pH from 7.3 to 6.0. Soil strength of Yurakucho silt increased slightly on decreasing pH to 6.0 but soil strength decreased significantly on reducing pH to 4. The mineralogy of the clay fraction as well as the concentration of acid in the pore fluid influenced the stress-strain behaviour of the soils [41].

A study was carried out by Prakash *et al.* to determine the effects of acid and base contamination on the geotechnical properties of clay [42]. 5%, 10%, 15%, 20%, 25% and 30% by weight of 1N Sodium hydroxide (NaOH), Potassium hydroxide (KOH), Calcium hydroxide (Ca(OH)₂), Hydrochloric acid (HCl), Nitric acid (HNO₃) and Sulphuric acid (H₂SO₄) were added to clay of high compressibility (CH) to study the effects of acid and base contamination on geotechnical properties of soil. On contamination with acid, liquid limit and plasticity index of clay sample decreased and it further decreased with increase in the percentage of acid content. The free swell of the acid contaminated soil increased by 28.27% whereas the specific gravity decreased by 15.56% with increase in acid content up to 30%. Optimum moisture content and maximum dry density of contaminated soil decreased by 21% and 12.7%, respectively on increasing acid content up to 30%. The shear strength of clay contaminated with acid decreases by 39.5% with increase in acid content upto 30%. No significant variation is reported in shrinkage limit values. At pH below 5.5, solubility of metal ion is increased and retention of metals to soil is reduced thus increasing its availability in soil solution [43].

In comparison to uncontaminated clay, liquid limit and plastic limit of base contaminated clay increase by 24.5% and 12.6%, respectively with increase in base content up to 30%. The plasticity index of contaminated soil also increased with increase in the percentage of base content. Free swell values of contaminated clay did not have significant variation with increase in base concentration. The optimum moisture content and maximum dry density decreased by 22% and 3.47%, respectively with increase in base contamination up to 30%. The specific gravity and shear strength of clay contaminated with base increases by 4.2% and 22.7%, respectively with increase in base content up to 30%.

Expansive reactions between lime and sulfate-bearing clay soils induced heave. Contamination of bentonite clay with caustic soda increases the negative charge on clay particle which is indicated by the enhanced exchangeable sodium content of the contaminated clay. Increase in negative charge results in expansion of the diffuse double layer

thickness responsible for higher liquid limit, swelling magnitude and swelling pressure of the contaminated clay. Increased negative charge leads to more oriented particle arrangement and lower shrinkage limit. Spillage of highly concentrated caustic soda solution caused structural damage to a building [44].

Contamination with salt

In coastal regions, due to tidal movement, sea water ingress into the land mass and in sea, soil is being retained in salty water thus making the soil mass contaminated with NaCl (main constituent of sea water). Due to civil engineering activities in coastal areas, in the shallow beds of seas or in deep sea, knowledge of engineering behaviour of soils on sea shore or sea bed become necessary for cost effective construction on such soils. Soil in coastal region is generally sandy.

Ramesh *et al.* reported that plasticity and compaction characteristics of fine grained soils changed significantly on addition of NaCl to it [45]. Maximum dry density, plasticity and unconfined compressive strength of cohesive soil contaminated with NaCl are reported to decrease while optimum moisture content got increased on contamination of soil with NaCl [46]. Ghosh *et al.* reported that sorption capacity, dielectric capacity and cation exchange capacity got increased considerably while surface area of the cohesive soils contaminated with NaCl got decreased with increasing concentration of sodium chloride [47]. George *et al.* reported that permeability of the cohesive soils contaminated with NaCl got increased significantly [48].

Datta *et al.* studied the effect of common salt on engineering properties of poorly graded sandy soil [49]. California Bearing Ratio (CBR) of the sand contaminated with NaCl is reported to increase from 6.7 to 8.1 on increasing concentration of NaCl from 0% to 10%. OMC of contaminated sand increased from 14 to 16 % on increasing the percentage of salts from 0 to 10 %. Maximum dry density of contaminated sand at optimum moisture content increased gradually on increasing concentration of NaCl from 0% to 5 % but the maximum dry density falls to a lower value when concentration of NaCl is increased to 10 %. When common salt was added to dry sand and compacted, the dry density showed a gradual increase in value with increase in NaCl concentration. In dry condition, the salt occupies void spaces and thereby increasing the dry density.

Contamination with EDTA

The effect of EDTA solution, used for remediation of Pb contaminated silty clay, on its engineering properties was studied by Wang *et al.* [50]. Due to industrialization, soil get contaminated by heavy metals, which reduce the soil fertility and is detrimental to animals and human health thus necessitating its remediation [51-54]. Phytoremediation, microbial remediation, chemical remediation, physical remediation and combination of physical separation and chemical extraction are being used to remediate soil contaminated with heavy metals [55]. Chemical leaching of heavy metals from contaminated soil by inorganic acids, organic acids, chelating agents and surfactant is reported to be very effective remediation

techniques [56-59]. Though inorganic acids effectively remove heavy metals from contaminated soil but it increase acidity of soil and degrade engineering properties of the soil [60]. Compressibility and expansion index of the soil contaminated with acid or alkali increase with the increase of acid or alkali concentration [61]. EDTA has higher removal efficiency for heavy metals such as copper, lead, cadmium and zinc in contaminated soil than acid [62,63]. Extraction efficiency of eluent for heavy metal contaminated soil followed the order EDTA> DTPA> NTA> HCl. Extraction efficiency of eluent increased with the increasing eluent concentration [64].

Ion exchange between contaminated soil and EDTA results in changing microstructure and engineering properties of soil. The pH of Pb contaminated soil was reduced on addition of EDTA solution and on increasing concentration of EDTA solution from 0 to 0.15mol/L, pH of soil decreased from 7.94 to 5.12. Disodium EDTA is an acidic salt so the solution of EDTA is acidic. When soil contaminated with Pb was remediated by EDTA solution, the H⁺ ions present in EDTA solution got adsorbed by the soil and the number of H⁺ ions adsorbed by soil increases on increasing concentration of EDTA solution, resulting in the decreased pH of soil.

On washing of soil contaminated with Pb by different concentration of EDTA solution, the liquid limit and plastic limit increased from 21.8% and 41.6% to 23.0% and 43.3%, respectively as concentration of EDTA increased from 0 to 0.15mol/L. Due to ions exchange, thickness of the diffuse double layer increased on increasing concentration of EDTA solution, causing increase in plastic limit and liquid limit of Pb contaminated soil.

X-ray diffraction results show that on increasing concentration of EDTA solution from 0 to 0.15mol/L, content of quartz in Pb contaminated soil increased by 11.09 percent and content of montmorillonite decreased from 7.87% to 0.07%. In comparison to montmorillonite, the content of albite and illite were not decreased much. On increasing concentration of EDTA solution, pH of soil is reduced, which is responsible for dissolution of montmorillonite, illite, and albite but quartz is relatively stable in acidic condition so its content got increased on increasing concentration of EDTA solution [65].

On increasing concentration of EDTA solution, cohesion of contaminated soil got decreased and the internal friction angle got increased. Cohesion of contaminated soil leached by water and 0.15mol/L EDTA were reported to be 89.5kPa and 40.67kPa, respectively. The soil cohesion is reduced on increasing thickness of diffused double layer. Thickness of diffuse double layer is increased on reduction of content of clay minerals due to increased concentration of EDTA solution [66]. The increased internal friction angle may be due to a change in soil composition. On increasing concentration of EDTA solution, coefficient of consolidation and modulus of compression got increased and void ratio decreased from 0.813 to 0.764.

Contamination with Industrial effluent

The effect of textile effluent, tannery effluent and battery effluent on the California Bearing Ratio (CBR) of expansive soil is reported by Narasimha Rao *et al.* [67].

Expansive soil was treated with textile effluent, tannery effluent and battery effluent at 0%, 20%, 40%, 60%, 80% and 100% by dry weight of the soil. The California Bearing Ratio (CBR) was determined corresponding to both 2.5 mm and 5.0 mm penetrations. The CBR of soil treated with tannery or textile effluent increased at 2.5 mm penetration and 5.0 mm penetration, which further increased with percent increase of effluent. Addition of battery effluent decreased CBR of expansive soil at 2.5 mm penetration and 5.0 mm penetration. The maximum percentage increase or reduction of CBR occurs when soil is treated with 100% of effluent.

The maximum percent increase in CBR values corresponding to 2.5 mm penetration and 5.0 mm penetration were about 50% and 45% respectively when the soil was treated with 100% tannery effluent. The maximum percent increase in CBR values corresponding to 2.5 mm penetration and 5.0 mm penetration are about 45% and 40% respectively when the soil was treated with 100% textile effluent. The maximum percent decrease in CBR values corresponding to 2.5mm penetration and 5.0mm penetration were about 21% and 17% respectively when the soil was treated with 100% battery effluent. Textile and tannery effluents can be used for stabilization of expansive soil but battery effluent is contaminating the soil.

Engineering properties of soil are controlled by thickness of diffused double layer, which is affected by pore fluid chemistry such as, electrolyte concentration, valency of ion, radius of hydrated ion etc. Treatment of soil with industrial effluents changes the pore fluid chemistry, which in turn changes engineering properties of soil.

On mixing of soil with tannery effluent, chromium ion present in the tannery effluent got adsorbed on to the clay particles, resulting in increasing the dry density of clay and decreasing double layer thickness. The reduction of the double layer thickness brings the clay particles closer and enhance stronger bonding between clay particles, which in turn increases the CBR values of the soil.

On mixing of expansive soil with textile effluent, the dry density of soil got decreased and optimum moisture content got increased. The chlorides in the textile effluent is attracted to the lower valence metallic ions in the clay mineral and causes decrease in double layer thickness. The decrease in double layer thickness causes increase in attractive forces leading to flocculated structure which causes dry density to decrease. Water holding capacity of soil got increased due to retention of water within the voids of flocculated structure, which in turn increases optimum moisture content. Strong bonding between clay mineral and dyes and cellulose of textile effluent may be responsible for increase in CBR values of soil treated with textile effluent.

On mixing of expansive soil with battery effluent, sulphate ions present in battery effluent got adsorbed on to the clay particles, making the surface of clay particles

negatively charged. Negatively charged clay particle surface can hold more quantity of water as double layer resulting in expansion of double layer thickness and increase in the distance between individual soil particles. Increased distance between clay particles reduces attractive forces for holding the soil particles together. Weak chemical bonding between clay minerals due to presence of reactive chemicals in battery effluent reduce the CBR values of soil.

Shrinkage limit decreases and liquid limit and plastic limits of clay soil contaminated with dye industry effluent increases with the increase in percentage of the effluent [68]. Free swell index and swelling pressure also increases with increase in percentage of effluent. Free swell values of uncontaminated and contaminated soil are reported to be 50% and 100%, respectively while swell pressure increased from 0.35 Kg/sq.cm. to 0.667 Kg/sq.cm. for contaminated soil. Contaminated soil is reported to have higher content of sodium, potassium, calcium, magnesium, copper and ferrous ion. Higher swelling potential of contaminated soil may be due to presence of high concentration of sodium ion in it. Shear strength increases on increasing the valency of cation and/or electrolyte concentration but shear strength decreases on increasing ionic size and/or dielectric constant of pore fluid.

CONCLUSION

As is clear from above discussion that a particular type of contaminant has different effect on different type of soil. Depending on the nature of contaminant, positive or negative effects of contaminant on the engineering properties of soils are possible. Industrial effluent discharged on the soil can improve or degrade engineering properties of soil thus affecting the stability of the supported structure. Improvement in engineering properties of soil due to presence of industrial waste in it, results in value addition to the industrial wastes by being used as a soil stabilizer but if industrial waste degrade engineering behaviour of soil then solution for decontamination of soil is to be searched. Planning suitable preventive and remedial measures for safe utilization of the industrial waste and contaminated soil is to be done. At the time of geotechnical projects designing, effect of contaminant on soil strength is to be taken into consideration [69].

References

1. Habib-ur-Rehman, Abduljauwad, S. N. and Akram T. (2007) "Geotechnical Behavior of Oil Contaminated Fine-Grained Soils", *Electronic Journal of Geotechnical Engineering EJGE*, Vol. 12, - Bundle A; 7-20.
2. Fine, P., Graber, E.R. and Yaron, B. (1997) "Soil interactions with petroleum hydrocarbons: abiotic processes", *Soil Technology*, Vol.10, pp. 133– 153.
3. Nudelman, N.S., Rios I.S. and Katusich, O. (2002) "Fate of the oil residuals in Patagonian soils effects of the environmental exposure time", *J. Environ. Assessment Remediation*, Vol.3, pp.1-8.
4. Lagaly, G. (1987) "Clay-Organic Interactions: Problems and Recent Results," *Proceedings,*

- International Clay Conference, pp. 343-351, The Clay Minerals Society, Bloomington, Indiana, USA.
5. P.V. Sivapullaiah, "Effects of soil pollution on geotechnical behaviour of soils", Indian Geotechnical Conference, Guntur, pp 933 - 940, 2009
 6. T.S. Umesh, H. D. Sharma, S. V. Dinesh, P.V. Sivapullaiah, Swamy.C. Basim, "Physico-Chemical Changes In Soil Due To Sulphuric Acid Contamination", *Indian Geotechnical Conference, Kochi*, Paper No.L-320, pp 765 – 768, 2011
 7. Gidigasu, M. D. and Kuma, D. O. K (1987). Geotechnical Characterization of Laterized Decomposed rocks for Pavement Construction in dry Sub-Humid Environment. Proc. 6th South East Asia Conf. on soil engineering, Taipei, Vol.1, pp. 493-506.
 8. Nabil F. Ismael and M.A. Mollah, Leaching effect on properties of cemented sand in Kuwait, *Journal of Geotechnical and Geoenvironmental Engineering* 124 (10) (1998) 997–1004.
 9. J.N. Meegoda and P. Ratnaweera, Compressibility of contaminated fine grained soils, *Geotechnical Testing Journal* 17 (1) (1994), 101-112.
 10. E. Sztompka, Biodegradation of engine oil in soil, *Acta Microbiologica Polonica*, 489 (1999) 185-196.
 11. J.J. Bowders and D.E. Daniel, Hydraulic conductivity of compacted clay to dilute organic chemicals, *Journal of Geotechnical Engineering ASCE* (1987) 1432-1448.
 12. K. Mashalah, H.C. Amir and M. Tajik, Effect of crude oil contamination on geotechnical properties of clay and sandy soil, *Engineering Geology* 89 (3-4), (2007), 220-229.
 13. B.M. Das, Principles of Geotechnical Engineering, third ed., PWS Publishing Company, 1994, 436p.
 14. Dorota Izdebska-Mucha, Jerzy Trzcin' ski, Effect of petroleum pollution on clay soil microstructure, *GEOLOGIA* 50 (Suppl.), (2008) S68–S74.
 15. K.M. Brown and D.C. Anderson, Effect of Organic Solvents on the Permeability of Clay Soils, EPA-600/2-83-016, Final Report, Solid and Hazardous Waste Res. Div. US Environ. Protection Agency, Cincinnati, Ohio, 1983.
 16. Ashraf K. Nazir, Effect of motor oil contamination on geotechnical properties of over consolidated clay, *Alexandria Engineering J.*, 2011, 50 331-335.
 17. J.K. Mitchell, Fundamentals of Soil Behaviour, John Wiley & Sons, Inc., New York, 1993, 437p.
 18. E.J. Verwey and J.T.G. Overbeek, Theory of the Stability of Lymphoid Colloids, Elsevier, Amsterdam-New York, 1948.
 19. Aiban, A. Saad (1997). "The Effect of Temperature on the Engineering Properties of Oil Contaminated Sand, *Environment International*, Vol. 24, No. 1/2, pp. 153-161.
 20. Evgin, E. and Das, B. M. (1992). "Mechanical Behaviour of an oil Contaminated Sand", *Envir Geotech*, Proc. Mediterranean Conf. Usmen and Acar, eds, Balkema Publishers, Rotterdam, The Netherlands pp. 101-108.
 21. Euchun, C. S. and Braja M. D., (2001). Bearing Capacity of Unsaturated Oil-Contaminated Sand, *International J. of Offshore and Polar Engineering*, Vol 11, No. 3, P.1
 22. Ukpong E. C and Umoh I. C; Effect of Crude Oil Spillage on Geotechnical Properties of Lateritic soil in Okoroete, Eestern Obololo, *International Journal of Engineering and Applied Sciences* June. 2015. Vol. 7. No. 01, 12-24.
 23. Ijimdiya, T. S. (2010) "The Effect of Compactive Effort on the Compaction Characteristics of oil Contaminated Lateritic Soils, *Int. J. of Engg.*, Vol. 4, No. 4. pp. 549-554.
 24. Anoliefo, A. M. (1991). The Effect of Hydrocarbon on the Engineering Properties of Lateritic Soil, *Int. J. of Engg.* Vol. 5, No. 4, pp. 328-332.
 25. Ijimdiya, T. S. (2010) "The effect of oil Contamination on Particle Size Distribution and Plasticity Characteristics of Lateritic Soils", *Advance Material Research*, vol. 367, pp. 19.
 26. Osinubi, K. J., Ijimdiya, T. S. and Kasai, K. J. (2007). "Evaluation of Strength of Reconstituted Laterite for Use as Liners and Covers" Book of Proc. Bi-monthly Material Society of Nigeria Conference, Zaria. Pp. 1-8, 1993.
 27. Amadi A., Abbey, S.A and Nma, A (1996) "Chronic effect of oil spill on soil Properties and micro flora of a rainforest ecosystem in Nigeria", *Water, Air and soil Pollution*, Vol.86, pp.1-11.
 28. A.T.Elisa, Effect of Crude Oil Contamination on the Geotechnical Properties of Soft Clay Soils of Niger Delta Region of Nigeria, *Electronic Journal of Geotechnical Engineering*, Vol. 17, 2012, Bundle M; 1929-1938.
 29. Khamchian, M., Charkhabi, A.M. & Tajik, M. (2007). Effects of crude oil contamination on geotechnical properties of clayey and sandy soils. *Eng. Geol.* 89: 220-229.
 30. Anoliefo, G O and Vwioko, D E (2001). Tolerance of Chromolaena odorata (L)K. and R. grown in soil contamination with spent lubrication oil, *Journal of Tropical Biosciences*, 1:20-24.
 31. Wang, J; Jiq, C R; Wong, C K and Wong, P K (2000), Characterisation of polycyclic aromatic hydrocarbons created in lubricating oils, *Water, Air and Soil Pollution*, 120: 381-396.
 32. Atuanya, E I (1987). Effect of waste engine oil pollution on physical and chemical properties of soil. A case study of waste oil contaminated Delta Soil in Bendel State, *Nigeria Journal of Applied Sciences*, 5:155-176.
 33. Okonokhua, B O; Ikhajiagbe, B; Anoliefo, G O and Emede, T O, The Effects of Spent Engine Oil on Soil Properties and Growth of Maize (*Zea mays L.*), *J. Appl. Sci. Environ. Manage. September*, 2007, Vol. 11 (3) 147 - 152.
 34. Ogboghodo, I.A., Iruaga, E.K. Osemwota, I.O. and Chokor, J.U. (2004) "An assessment of the effects of crude oil pollution on soil properties, germination and growth of maize (*Zea Mays*) using two crude types; Forcados light and escravos light", *J. Environ. Monitoring and Assessment*, 96: pp.143-152.

35. Vwioko, D E; Anoliefo G O and Fashemi, S D (2006), Metals concentration in plant tissues of *Ricinus communis* L. (Castor Oil) grown in soil contaminated with spent lubricating oil, *J. of Applied Science and Environmental Management*, 10: 127-134.
36. Yong, R N (2001). Geoenvironmental engineering: contaminated soils, pollutant fate And mitigation, CRC Press, Florida, 307 pp.
37. Sridharan, A, Nagraj, T.S., and Sivapullaiah, P.V. "Heaving of soil Due to Acid Contamination" Proc. of the X ICSMFE, Stockholm, Vol.2, 383-386. (1981)
38. Ivan B. Gratchev, Ikuo Towhata, " Effects of Acidic Contamination on the Geotechnical Properties of Marine Soils in Japan", International Offshore and Polar Engineering Conference, pp 151 – 154, 2009
39. Joshi, R.C., Pan., and Lohita, P. "Volume Change in Calcareous Soils due to Phosphoric acid, Contamination", Proc. Of the XIII ICSMFE, New Delhi, Vol.4, 1569-1574, 1994.
40. Ivan Gratchev and Ikuo Towhata, Compressibility of natural soils subjected to long-term acidic contamination, *Environmental Earth Sciences*, September 2011, Volume 64, Issue 1, pp 193-200.
41. Ivan Gratcheva and Ikuo Towhatab, Stress-strain characteristics of two natural soils subjected to long-term acidic contamination, *Soils and Foundations* Volume 53, Issue 3, June 2013, Pages 469-476.
42. S. Prakash and P. D. Arumairaj, Effects of Acid and Base Contamination on Geotechnical Properties of Clay, *International Journal of Science and Research*, Volume 4 Issue 5, May 2015, 1440-1444.
43. McBride, M B (1994). Environmental chemistry of soils. New York, Oxford University Press, 406 pp.
44. Kumapley, N.K. and Ishola, A., "The Effect of Chemical Contamination on Soil Strength" Proc. of the XI ICSMFE, Sanfrancisco, Vol.3, 1199-1201, 1985.
45. Ramesh H.N., Nanda H.S., Muddaraja H.C. and Manojkrishna K.V.(2004). Effect of R.F.A. and sodium salts on the index and compaction properties of shedy soil, *Indian Geotectectical Conference, Vol I, Warengal*, 297-300.
46. Kumar S., Malyala V.N., Mohanti M. and Das B.N.(2006), Treatment of high plastic clays using Sodium Chloride. *Proc. Indian Geotectectical Conference, Vol I*, 297-300.
47. Ghosh S., Gangopadhyay A. and Halder S. (2003), Identification and characterization of contaminated soils. *Proc. Indian Geotectectical Conference, Geotechnica Engineering for Infrastructural Development, Roorke Vol I*, 213-216.
48. George S., Jose B.T. and Abraham B.M.(2003) Significance of Diffused Double Layer on Permeability of clay liners. *Proc. Indian Geotectectical Conference, Geotechnical Engineering for Infrastructural Development, Roorke Vol I*, 225-228.
49. Datta, T. and Chottopadyaya, B.C. Variations of Engineering Properties of Soils Affected by Sea Ingression, Indian Geotechnical Conference – 2010, *GEOTrendz*, December 16-18, 2010, IGS Mumbai Chapter & IIT Bombay.
50. Ping Wang, Jiang-shan Li and Hua-fang Wang, Engineering Properties of Heavy Metal Contaminated Soil Affected by EDTA Washing, *Electronic Journal of Geotechnical Engineering*, VOL.18, 2013, Bundle R, 3909-3918.
51. Zheng, X. S., Lu, A. H., Gao, X., Zhao, J., Zheng, D. S. (2002) "Contamination of heavy metals in soil present situation and method," *Soil and Environmental Sciences*, 11(1): 79-84.
52. Cui, D. J. and Zhang, Y. L. (2004) "Current Situation of Soil Contamination by Heavy Metals and Research Advances on the Remediation Techniques," *Chinese Journal of Soil Science*, 35(3): 366-370.
53. Yao, Z. T., Li, J. H., Xie, H. H., Yu, C. H. (2012) "Review on Remediation Technologies of Soil Contaminated by Heavy Metals," *Procedia Environmental Sciences*, 16: 722-729.
54. Kong, C. Y. (2008) "Research on Chemical Washing Remediation Effect of Heavy Metal Contaminated Soils." *Journal of Dezhou University*, 24(6): 50-54.
55. Wang, X. H., Liu, Y. G., Zeng, G. M., Zhou, C. H., Li, X., Fan, T., Zuo, M. (2006) "Extraction of Heavy Metals from Contaminated Soil with EDTA and Their Redistribution of Fractions," *Environmental Science*, 27(5): 1008- 1012.
56. Sun, B., Zhao, F. J., Lombi, E. and Mcgrath, S. P. (2001) "Leaching of heavy metals from contaminated soils using EDTA," *Environmental Pollution*, 113(2): 111- 120.
57. Dermont, G., Bergeron, M., Mercier, G., Richer-Lafleche, M. (2008) "Soil washing for metal removal: A review of physical/chemical technologies and field applications," *Journal of Hazardous Materials*, 152 (1): 1-31.
58. Ke, X., Li, P. J., Gong, Z. Q., Yin, W., Su, D. (2004) "Advances in flushing agents used for remediation of heavy metal contaminated soil," *Chinese Journal of Ecology*, 23(5): 145-149.
59. Li, Y. M., Lei, M., Chen T. B., Yang, J., Zhou, X. Y., Guo, Q. J., Ma, J. (2011) "The selection of eluting agents in remediation of the heavy metal polluted soil left by a steel plant," *Ecology and Environmental Sciences*, 20(4): 696-700.
60. Pichtel, J., Vine, B., Kuula-Väisänen, P. and Niskanen, P. (2001) "Lead extraction from soils as affected by lead chemical and mineral forms," *Environmental Engineering Science*, 18(2): 91-98.
61. Zhu, C. P., Liu, H. L. and Zhang, X. L. (2008) "Laboratory tests on compression characteristics of soil polluted by acid and alkali," *Chinese Journal of Geotechnical Engineering*, 30 (10): 1477-1483.
62. Li, F. S., Han, M., Xiong, D. Q., Lu, G. F., Liu, F., Zhao, B. Q. and Zhang, F. D. (2003) "Efficiency of Some Extractants for Available Heavy Metals from Several Typical Soils," *Journal of Agro-Environment Science*, 22(6): 704-706.

63. Robert, W. P. (1999) "Chelant extraction of heavy metals from contaminated soils," *Journal of Hazardous Materials*, 66, 151-210.
64. Chen, X. T., Wang. X. and Chen, X. (2005) "Study on the Exaction Efficiency of Heavy Metals by Chelates," *Jiangsu Environmental Science and Technology*, 18(2): 9-10, 13
65. Zhu, C. P. and Liu, H. L. (2007) "Study on engineering properties of polluted soil," *Rock and Soil Mechanics*, 3(28): 625-630.
66. Xiang, W., Cui, D. S. and Liu, L. (2007) "Experimental Study on Sliding Soil of Ionic Soil Stabilizer-Reinforces," *Earth Science: Journal of China University of Geosciences*, 32(13): 397-402.
67. Narasimha Rao A.V. and Chittaranjan M., *Int. J. of Engg. Inventions*, vol 1, issue 7 Oct 2012, 22-28.
68. D. L. Shah and A. V. Shroff, "Effects of Effluents of Industrial Waste on Soil Properties (A Case Study of Nandesari Area, Vadodara)" , March 9-12, 1998, Proceedings: Fourth International Conference on Case Histories in Geotechnical Engineering, St. Louis, Missouri, Paper 5.
69. P.V. Sivapullaiah, "Effects of soil pollution on geotechnical behaviour of soils", Indian Geotechnical Conference, Guntur, pp 933 - 940, 2009
